LABOR SERVICES DIVISION[875]

Notice of Intended Action

Proposing rule making related to hoistway lighting and conduit and providing an opportunity for public comment

The Elevator Safety Board hereby proposes to amend Chapter 71, "Administration of the Conveyance Safety Program," Chapter 72, "Conveyances Installed On or After January 1, 1975," and Chapter 73, "Conveyances Installed Prior to January 1, 1975," Iowa Administrative Code.

Legal Authority for Rule Making

This rule making is proposed under the authority provided in Iowa Code section 89A.3.

State or Federal Law Implemented

This rule making implements, in whole or in part, Iowa Code chapter 89A.

Purpose and Summary

These proposed amendments would require additional lighting and conduit for hoistways of new elevators; also, when an elevator controller is being replaced, additional hoistway lighting would be required.

Fiscal Impact

The estimated installation cost for hoistway lighting is \$100 per floor. Conduit is typically part of the package for a new elevator, but some elevator mechanics do not use the conduit. Labor costs to install the conduit are minimal.

Jobs Impact

After analysis and review of this rule making, no impact on jobs has been found.

Waivers

Any person who believes that the application of the discretionary provisions of this rule making would result in hardship or injustice to that person may petition the Board for a waiver of the discretionary provisions, if any, pursuant to 875—Chapter 66.

Public Comment

Any interested person may submit written comments concerning this proposed rule making. Written comments in response to this rule making must be received by the Board no later than 4:30 p.m. on November 14, 2018. Comments should be directed to:

Kathleen Uehling Division of Labor Services 1000 East Grand Avenue Des Moines, Iowa 50319-0209

Email: kathleen.uehling@iwd.iowa.gov

Public Hearing

If requested, a public hearing at which persons may present their views orally or in writing will be held as follows:

November 14, 2018 11 a.m.

150 Des Moines Street Des Moines, Iowa

Persons who wish to make oral comments at the public hearing may be asked to state their names for the record and to confine their remarks to the subject of this proposed rule making.

Any persons who intend to attend the public hearing and have special requirements, such as those related to hearing or mobility impairments, should contact the Board and advise of specific needs.

Review by Administrative Rules Review Committee

The Administrative Rules Review Committee, a bipartisan legislative committee which oversees rule making by executive branch agencies, may, on its own motion or on written request by any individual or group, review this rule making at its regular monthly meeting or at a special meeting. The Committee's meetings are open to the public, and interested persons may be heard as provided in Iowa Code section 17A.8(6).

The following rule-making actions are proposed:

ITEM 1. Adopt the following \underline{new} definition of "Center of the elevator path" in rule 875—71.1(89A):

"Center of the elevator path" means a vertical line through the center point of an elevator car top beginning 2 feet below the lower landing and ending 10 feet above the highest landing of an elevator.

ITEM 2. Adopt the following **new** subrules 72.10(3) and 72.10(4):

72.10(3) Permanent lighting shall be installed in the hoistway of an elevator contracted after March 1, 2019. Three-way switches to control the hoistway lighting shall be installed at the pit access door and the top landing access door. The lighting shall be sufficient to provide 10 foot-candles of light to the center of the elevator path measured when the car top lights are off. Engineering calculations that prove 10 foot-candles of light are provided to the center of the elevator path may be substituted for light meter measurements under circumstances such as a glass back car where use of a light meter is not practical.

72.10(4) For conveyances contracted after March 1, 2019, all electrical wiring in a machine room, control space, control room, machinery space, and hoistway shall comply with ANSI/NFPA 70 and shall be enclosed in metal conduit, flexible conduit, or metal raceways. However, this subrule shall not apply in applications such as traveling cables and car top work lights where movement is required for proper function, or to operating devices and control equipment where adjustment may be needed.

ITEM 3. Adopt the following **new** subrule 72.13(7):

72.13(7) Hoistway lighting. If the controller for an elevator is being replaced, permanent lighting shall be installed in the hoistway of the elevator. Three-way switches to control the hoistway lighting shall be installed at the pit access door and the top landing access door. The lighting shall be sufficient to provide 10 foot-candles of light to the center of the elevator path measured when the car top lights are off. Engineering calculations that prove 10 foot-candles of light are provided to the center of the elevator path may be substituted for light meter measurements under circumstances such as a glass back car where use of a light meter is not practical.

ITEM 4. Adopt the following **new** subrule 73.8(8):

73.8(8) Hoistway lighting. If the controller for an elevator is being replaced, permanent lighting shall be installed in the hoistway of the elevator. Three-way switches to control the hoistway lighting shall be installed at the pit access door and the top landing access door. The lighting shall be sufficient to provide 10 foot-candles of light to the center of the elevator path measured when the car top lights are off. Engineering calculations that prove 10 foot-candles of light are provided to the center of the elevator path may be substituted for light meter measurements under circumstances such as a glass back car where use of a light meter is not practical.